GENERATOR KING

GKS-265
SCANIA 250KVA

250kVA Prime / **265kVA** Standby

Comprehensive Specification Sheet
Electrical and Mechanical Data

SCANIA

3ph

GKS-265
SCANIA 250KVA

250kVA Prime / **265kVA** Standby / **Three Phase**

FEATURES & BENEFITS

- 265kVA standby power at 230/400v @ 50Hz 1500rpm
- High-quality and reliable five-cylinder (in-line) 9.3l turbocharged Scania diesel engine
- Ideal for home and business applications
- Silent canopy which can stand outside with lockable doors
- Automatic changeover (ATS), maintenance free batteries and trickle charger included
- H-specification insulation, brushless alternator with AVR provides stable output
- High-temperature and oil pressure sensor to protect against engine damage
- Easy to use digital controller with auto/manual start options
- All sets undergo a comprehensive testing/pre-delivery inspection prior to delivery
- Peace of mind of earlier of one year/1000 hour warranty

CANOPY

- Ventilation parts are designed with modular principles
- Weather resistant and lined with sound reducing foam
- All metal canopy parts are painted with powder paint
- Panel window
- Lockable doors on each side
- Easy maintenance and operation
- Easy lifting and moving
- Thermally insulated engine exhaust system
- Exterior emergency stop push button
- Sound attenuated

CHASSIS

- The complete generator set is mounted as a whole on a heavy duty fabricated, steel base frame
- Steel chassis and anti-vibration pads
- Base frame design incorporates an integral fuel tank
- The generator can be lifted or carefully pushed/pulled by the base frame
- Dial type fuel gauge on the fuel tank

Overview

Standby power	**265kVA**
Prime power	**250kVA**
Phase	**Three**
Dry weight	**3400kg**
Length	**3400mm**
Width	**1400mm**
Height	**1850mm**
Fuel tank capacity	**600l**

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

AUTO MAINS FAILURE CONTROL PANEL

- Controller with Smartgen automatic transfer switch
- Smartgen HGM7220 electronic controller
- Emergency stop push button
- Static battery charger
- Four-pole electrically and mechanically interlocked ATS

GENERATING SET CONTROL MODULE SMARTGEN HGM7220 FEATURES

- This module is used to monitor a mains supply and automatically start a standby generating set
- Shutdown alarms
- STOP/RESET-MANUAL-AUTO-TEST-START

METERING VIA LCD DISPLAY

- Mains volts (L-L/L-N)
- Generator amps (L1, L2, L3)
- Generator frequency; generator (cos)
- Engine hours run; plant battery (volts)
- Engine oil pressure (psi and bar)
- Engine speed (rpm)
- Engine temperature (degrees C)

AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

- Under/over speed; fail to start
- High engine temperature; fail to stop
- Low oil pressure; charge fail
- Under/over generator volts
- Under/over generator frequency
- Emergency stop/start failure
- Under/over mains voltage
- Charge failure

GKS-265
SCANIA 250KVA

250kVA Prime / **265kVA** Standby / **Three Phase**

TECHNICAL SPECIFICATIONS

*All ratings are quoted at maximum ratings at sea level and derating will be applicable for altitude and power factor.

Engine

Engine make	**Scania**
Engine model	**DC09 072-Ref 02-11**
Displacement	**9.3l**
Cylinder bore/Stroke	**130mm x 140mm**
Fuel system	**In-line fuel injection pump**
Governor	**Electrical**
Cylinders	**Five in-line cylinders water cooled**
Engine output power (1500rpm)	**226kW**
Turbocharged/normally aspirated	**Turbocharged**
Cycle	**Four stroke**
Combustion system	**Direct injection**
Compression ratio	**16:1**
Fuel tank capacity	**600l**
Fuel consumption 100%	**51.85 l/h**
Fuel consumption 75%	**38.14 l/h**
Fuel consumption 50%	**26.37 l/h**
Fuel consumption 25%	**13.18 l/h**
Oil type	**CD-15W-40**
Engine oil capacity	**31 - 36dm³**
Cooling method	**Water-cooled radiator/fan**
Coolant capacity (including radiator)	**38l**
Starter	**24v DC charge alternator**
Engine speed	**1500rpm**
Filters	**Replaceable fuel filter/oil filter/dry element air filter**
Battery	**Maintenance-free battery including rack and cables**
Silencer	**Exhaust silencer**

Alternator

Alternator make	**StromerPower**
Standby power output	**265kVA**
Prime power output	**250kVA**
Insulation class	**Class-H with circuit breaker protection**
Type	**Brushless**
Phase and connection	**Three phase/four wire**
AVR	**Included**
AVR model	**SX460**
Voltage regulation	**± 1%**
Voltage	**230/400v**
Rated frequency	**50Hz**
Voltage regulate change	**≤ ±10% UN**
Phase change rate	**± 1%**
Power factor	**0.8φ**
Protection class	**IP23 standard/screen protected/drip-proof**
Stator	**2/3 pitch**
Rotor	**Single bearing**
Excitation	**Self-exciting**
Regulation	**Self-regulating**

General

Structure type	**Silent weather resistant enclosure**
Dimensions Length x Width x Height	**3400mm x 1400mm x 1850mm**
Dry weight	**3400kg**
ATS unit included	**Included**
Four-way protection system included	**Included**

The Generator King (Pty) Ltd | www.genking.co.za | sales@genking.co.za
+27 11 312 4673 | 50 Falcon Lane, Lanseria Corporate Estate, Lanseria, 1739

The Generator King (Pty) Ltd reserves the right to change generator information without prior notice. Information is double checked to ensure that it is correct, however The Generator King (Pty) Ltd will not be held responsible for clerical errors. (E&OE)