



GENERATOR KING

GKSD-66

SDEC 60KVA

60kVA Prime / 66kVA Standby

Comprehensive Specification Sheet
Electrical and Mechanical Data



3ph

GKSD-66

SDEC 60KVA

60kVA Prime / 66kVA Standby / Three Phase

FEATURES & BENEFITS

- 66kVA standby power at 230/400v @ 50Hz 1500rpm
- High-quality and reliable four-cylinder 4.3l turbocharged SDEC diesel engine
- Ideal for home and business applications
- Silent canopy which can stand outside with lockable doors
- Automatic changeover (ATS), maintenance free batteries and trickle charger included
- H-specification insulation, brushless alternator with AVR provides stable output
- High-temperature and oil pressure sensor to protect against engine damage
- Easy to use digital controller with auto/manual start options
- All sets undergo a comprehensive testing/pre-delivery inspection prior to delivery
- Peace of mind of earlier of one year/1000 hour warranty



CANOPY

- Ventilation parts are designed with modular principles
- Weather resistant and lined with sound reducing foam
- All metal canopy parts are painted with powder paint
- Panel window
- Lockable doors on each side
- Easy maintenance and operation
- Easy lifting and moving
- Thermally insulated engine exhaust system
- Exterior emergency stop push button
- Sound attenuated

CHASSIS

- The complete generator set is mounted as a whole on a heavy duty fabricated, steel base frame
- Steel chassis and anti-vibration pads
- Base frame design incorporates an integral fuel tank
- The generator can be lifted or carefully pushed/pulled by the base frame
- Dial type fuel gauge on the fuel tank

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

AUTO MAINS FAILURE CONTROL PANEL

- Controller with Smartgen automatic transfer switch
- Smartgen HGM6120N electronic controller
- Emergency stop push button
- Static battery charger
- Four-pole electrically and mechanically interlocked ATS

GENERATING SET CONTROL MODULE
SMARTGEN HGM6120N FEATURES

- This module is used to monitor a mains supply and automatically start a standby generating set
- Shutdown alarms
- STOP/RESET-MANUAL-AUTO-TEST-START

METERING VIA LCD DISPLAY

- Mains volts (L-L/L-N)
- Generator amps (L1, L2, L3)
- Generator frequency; generator (cos)
- Engine hours run; plant battery (volts)
- Engine oil pressure (psi and bar)

Overview

Standby power	66kVA
Prime power	60kVA
Phase	Three
Dry weight	1208kg
Length	2400mm
Width	1050mm
Height	1400mm
Fuel tank capacity	290l

- Engine speed (rpm)
- Engine temperature (degrees C)

AUTOMATIC SHUTDOWN AND
FAULT CONDITIONS

- Under/over speed; fail to start
- High engine temperature; fail to stop
- Low oil pressure; charge fail
- Under/over generator volts
- Under/over generator frequency
- Emergency stop/start failure
- Under/over mains voltage
- Charge failure

GKSD-66

SDEC

60KVA

60kVA Prime / 66kVA Standby / Three Phase

TECHNICAL

SPECIFICATIONS

*All ratings are quoted at maximum ratings at sea level and derating will be applicable for altitude and power factor.

Engine

Engine make	SDEC
Engine model	4HT4.3-G22
Displacement	4.3l
Cylinder bore/Stroke	105mm x 124mm
Fuel system	In-line fuel injection pump
Governor	Electronic
Cylinders	Four cylinders water cooled
Engine output power (1500rpm)	62kW
Turbocharged/normally aspirated	Turbocharged
Cycle	Four stroke
Combustion system	Direct injection
Compression ratio	16.0:1
Fuel tank capacity	290l
Fuel consumption 100%	15.1 l/h
Fuel consumption 75%	11.8 l/h
Fuel consumption 50%	8.1 l/h
Fuel consumption 25%	4.9 l/h
Oil type	15W-40
Engine oil capacity	13l
Cooling method	Water-cooled radiator/fan
Coolant capacity	17l
Starter	24v DC charge alternator
Engine speed	1500rpm
Filters	Replaceable fuel filter/oil filter/dry element air filter
Battery	Maintenance-free battery including rack and cables
Silencer	Exhaust silencer

Alternator

Alternator make	StromerPower
Standby power output	66kVA
Prime power output	60kVA
Insulation class	Class-H with circuit breaker protection
Type	Brushless
Phase and connection	Three phase/four wire
AVR	Included
AVR model	SX460
Voltage regulation	± 1%
Voltage	230/400v
Rated frequency	50Hz
Voltage regulate change	≤ ±10% UN
Phase change rate	± 1%
Power factor	0.8φ
Protection class	IP23 standard/screen protected/drip-proof
Stator	2/3 pitch
Rotor	Single bearing
Excitation	Self-exciting
Regulation	Self-regulating

General

Structure type	Silent weather resistant enclosure
Dimensions Length x Width x Height	2400mm x 1050mm x 1400mm
Dry weight	1208kg
ATS unit included	Included
Four-way protection system included	Included